

**HR Hexa Tech EN 14399-3 e EN 14399-6**

**Classe 8.8**

**ZINCATE A CALDO**



**Assieme Vite + Dado + Doppia rondella  
 ad alta resistenza a serraggio controllato**

**K2 CE**

(Lavorano per attrito)

**Art. 6060**

**Prezzi in €uro per 100 pezzi**

L = lungh. in mm	M12	M14	M16	M18	M20	M22	M24	M27	M30
<b>30</b>	144,88								
<b>40</b>	177,05	207,61	250,47	285,65	320,31				
<b>50</b>	184,15	218,80	264,93	285,65	366,95				
<b>60</b>	193,45	228,36	275,02	330,13	381,40	436,53	535,85		
<b>70</b>		241,60	289,75	343,22	398,88	455,88	611,14	1607,12	1704,68
<b>80</b>		253,19	297,11	347,87	416,35	472,80	637,07	1672,46	1754,11
<b>90</b>				360,95	434,64	522,64	657,79	1723,16	1811,43
<b>100</b>					446,08	549,21	677,44	1773,50	1864,19
<b>110</b>							700,14	1825,65	1924,74
<b>120</b>							716,45	1876,72	1984,84
<b>130</b>									
<b>140</b>									
<b>150</b>									
<b>160</b>									